



TECHNICAL DATA			
EXTERNAL DIMENSIONS	STANDARD		LS
width	420mm		
depth	490mm		
height	650mm		
WEIGHT	30 kg		
VOLTAGE	230V 50Hz		
POWER REQUIRED	2590 W		2800 W
WATER HARDNESS	2-8 °F		
INLET WATER PRESSURE	200-400 kPa		
CROCKERY DIMENSIONS			
plates diameter	---		280mm
dishes max. height	275mm		
RACK DIMENSION	370X370mm		
RACK EQUIPMENT	2XC10 - 1X10728 - 1X15060		
WASHING CYCLES (sec)	1 (120)		
WATER SUPPLY 55°C			
racks/h(*) ⁽¹⁾	30		
WATER SUPPLY 10°C			
racks/h(*) ⁽¹⁾	14		
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	1.8 L		
BOILER CAPACITY	3 L		
BOILER HEATING ELEMENT	2400 W		
RINSING TEMPERATURE (SET)	85°C		
TANK CAPACITY	12.5 L		
TANK HEATING ELEMENT	1250 W		
TANK TEMPERATURE (SET)	55°C		
PUMP POWER	190 W (120 L/min ^{***})		400 W (185 L/min ^{***})
DRAIN PUMP (optional)	25 W h MAX draining 0.8m (40 L/min ^{***})		
NOISE (dB(A)±0.7)	60.6		61.2

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.